

# PAN-307 Receipt Printer



the POS Printer you trust

## Bullet-points

Print method: Direct Thermal  
Print speed: 230mm  
Resolution: 576dots/line or 572dots/line  
(Printing width: 80mm(max)/72mm(default)  
Interface: USB + Serial + LAN  
Input buffer: 256kbytes  
NF Flash: 256kbytes  
Font A: 12x24  
Font B: 9x17  
Barcode 1D: UPC-A/UPC-E/JAN13/EAN13/JAN8/EAN8/CODE39/  
ITF/ CODABAR/CODE93/CODE128  
Barcode 2D: QR Code  
Paper type: Thermal Receipt Paper  
Paper width: 48mm/52mm/56mm/64mm/68mm/76mm/80mm  
Paper thickness: 0.06~0.08mm  
Roll Dia: Max. Ø 83 mm  
Paper load: Easy paper loading  
Paper Cut: Auto-cutter  
Working condition: 0°C~45°C, 10%~80%RH  
Storage condition: -10°C-60°C, 10%~90%RH  
Printing head: 150KM  
Cutter: 1.5million  
Emulation: ESC/POS  
Driver: Windows XP /Vista/ Win7/Win8 /Win10/Win 2000/Win CE/  
OPOS/JPOS  
SDK: Android, IOS



t: 25583271 e: info@ps-pos.com w: www.ps-pos.com